

## DX<sup>®</sup>10

### Metal-Polymer Plain Bearings Grease Lubricated



#### CHARACTERISTICS

- Perfect for heavy duty and harsh environments
- Excellent chemical resistance
- Excellent erosion resistance
- Good fatigue strength
- Good wear performance
- Can be broached for tighter tolerance
- Lead-free material compliant to EVL, RoHS and WEEE specifications

#### AVAILABILITY

**Bearing forms made to order:** cylindrical bushes, thrust washers, sliding plates, half-bearings, special shapes obtained by stamping, bearings with locating notches, lubricant holes and machined grooves, customized bearing designs




#### APPLICATIONS

**General:** Greased or oiled applications with high load, high temperature, and contamination; ideal for replacing bi-metal or bronze bushings to achieve improved wear performance

**Automotive:** King pins, oil pumps

**Industrial:** Piston pumps, agriculture equipment, construction, lift and cranes, small reciprocating bushing



## DX<sup>®</sup>10 Technical Data

Bearing Properties		Imperial Units	Imperial Value	Metric Units	Metric Value
<b>General</b>					
Maximum load, p	Static	psi	36 000	N/mm <sup>2</sup>	250
	Dynamic	psi	20 000	N/mm <sup>2</sup>	140
Operating temperature	Min	°F	- 40	°C	- 40
	Max	°F	350	°C	175
<b>Grease Lubricated</b>					
Maximum sliding speed, U		fpm	500	m/s	2.5
Maximum pU factor		psi x fpm	80 000	N/mm <sup>2</sup> x m/s	2.8
Coefficient of friction			0.01 - 0.10		0.01 - 0.10
<b>Oil Lubricated</b>					
Maximum sliding speed, U		fpm	2 000	m/s	10.0
Maximum pU factor		psi x fpm	80 000	N/mm <sup>2</sup> x m/s	2.8
Coefficient of friction			0.01 - 0.06		0.01 - 0.06
<b>Recommendations</b>					
Shaft surface roughness, Ra		µin	≤ 16	µm	≤ 0.4
Shaft surface hardness	Normal	HB	> 200	HB	> 200
	For longer service life	HB	> 350	HB	> 350

### Operating Performance

Dry	Fair
Oil lubricated	Very Good
Grease lubricated	Very Good
Water lubricated	Poor
Process fluid lubricated	Fair

### For Superior Performance

Dry	GAR-MAX / HSG / GAR-FIL / MLG
Water lubricated	HPF / HPM / DP4-B
Process fluid lubricated	DP4 / HI-EX / GAR-FIL

### Microsection

